



**201-8**

**HEAVY DUTY SPACE THERMOSTATS  
FOR HEATING AND COOLING**

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

**FEATURES**

- Dust, moisture and vermin resistant heavy metal case.
- No leveling required – Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.
- Extra rugged switch mechanism.

**SPECIFICATIONS**

Dimensions . . . . . 5<sup>3</sup>/<sub>8</sub>" H + 2<sup>1</sup>/<sub>2</sub>" coil x 2<sup>5</sup>/<sub>16</sub>" W x 2<sup>9</sup>/<sub>16</sub>" D  
 Finish . . . . . Grey color  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Valves and Relays		Resistive	
					120 VAC	240 VAC	120 VAC	240 VAC	120 VAC	240 VAC
201-8	20 to 90°F (-7 to +32°C)	Adj. 3 to 20°F (2 to 11°C)	Close on Rise	FGH See page 416	16.0A	8.0A	5.6A	2.8A	25.0A	22.0A
201-20	-30 to +90°F (-34 to +32°C)	Adj. 4 to 20°F (2 to 11°C)	Close on Rise	FGH See page 416	16.0A	8.0A	5.6A	2.8A	25.0A	22.0A
2A37-1	20 to 90°F (-7 to +32°C)	Adj. 3 to 20°F (2 to 11°C)	Open on Rise	FG See page 416	14.0A	7.0A	5.6A	2.8A	25.0A	22.0A



**259-6**

**HEAVY DUTY SPACE THERMOSTATS  
FOR HEATING AND COOLING**

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

**FEATURES**

- Dust, moisture and vermin resistant heavy metal case.
- No leveling required – Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.
- Extra rugged switch mechanism.

**SPECIFICATIONS**

Finish . . . . . Grey color  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Valves and Relays		Resistive	
					120 VAC	240 VAC	120 VAC	240 VAC	120 VAC	240 VAC
259-6 ①	Low Speed: 35 to 110°F (2 to +43°C)	Fixed 3°F (1.5°C)	Close on Rise	HH See page 416	7.4A	3.7A	2.9A	1.4A	7.4A	3.7A
	High Speed: 35 to 110°F (2 to +43°C)	Fixed 4°F (2.2°C)	SPDT	HH See page 416	7.4A	3.7A	2.9A	1.4A	7.4A	3.7A

① 259-6 has plastic coated copper element

✻ Indicates Canadian Model Number: call 1-800-305-6953 to order